



## PRO-PLOW® Series 2 Specifications

### Technical Specifications

Imperial	7' 6	8'	8' 6	POLY 7' 6	POLY 8'
Blade Width	7' 6"	8'	8' 6"	7' 6"	8'
Blade Height	29"	29"	29"	29"	29"
Blade Gauge	11	11	11	3/8" poly	3/8" poly
Trip Springs	4	4	4	4	4
Shock Absorbers	1	1	1	1	1
Vertical Ribs	7	7	7	7	7
Angling Rams	1½" x 10"	1½" x 10"	1½" x 10"	1½" x 10"	1½" x 10"
Plowing Width (full angle)	6' 6"	6' 11"	7' 4"	6' 6"	6' 11"
Approx. Weight (less mount)	653 lb	668 lb	686 lb	677 lb	690 lb
Disc Shoes	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
Cutting Edge	3/8" x 6"	3/8" x 6"	3/8" x 6"	3/8" x 6"	3/8" x 6"
Mount Type	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount® 2
Lift Cylinder	1½" x 8"	1½" x 8"	1½" x 8"	1½" x 8"	1½" x 8"

Metric	7' 6	8'	8' 6	POLY 7' 6	POLY 8'
Blade Width	2.29 m	2.44 m	2.59 m	2.29 m	2.44 m
Blade Height	73.66 cm	73.66 cm	73.66 cm	73.66 cm	73.66 cm
Blade Gauge	3.18 mm	3.18 mm	3.18 mm	9.52 mm	9.52 mm
Trip Springs	4	4	4	4	4
Shock Absorbers	1	1	1	1	1
Vertical Ribs	7	7	7	7	7
Angling Rams	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Plowing Width (full angle)	1.98 m	2.11 m	2.24 m	1.98 m	2.11 m
Approx. Weight (less mount)	296 kg	302 kg	311 kg	307 kg	312 kg
Disc Shoes	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
Cutting Edge	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm
Mount Type	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount® 2	UltraMount® 2
Lift Cylinder	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm	3.81 cm x 20.32 cm