



## Striker™ Specifications

### Technical Specifications

Imperial	7' 1.5 cu yd	8' 2.0 cu yd	9' 3.0 cu yd	9' 4.5 cu yd	10' 4.5 cu yd	10' 6.0 cu yd
Body Side Length	7'	8'	9'	9'	10'	10'
Capacity	1.5 cu yd	2.0 cu yd	3.0 cu yd	4.5 cu yd	4.5 cu yd	6.0 cu yd
Hopper Construction	16 ga SS	16 ga SS	16 ga SS	16 ga SS	16 ga SS	16 ga SS
Dimensions Overall (LxWxH)	84" x 50" x 38"	96" x 50" x 33"	108" x 50" x 41"	108" x 70" x 47"	120" x 70" x 47"	120" x 70" x 54"
Dual 12V DC Sealed Motors	595 lb	615 lb	695 lb	815 lb	--	--
Gas 10.5 hp I/C Briggs & Stratton®	--	740 lb	820 lb	940 lb	965 lb	1010 lb
Gas 11 hp I/C Honda®	--	740 lb	820 lb	940 lb	965 lb	1010 lb
Dual Hydraulic Motors	--	615 lb	695 lb	815 lb	840 lb	885 lb
Conveyor Width	16 ½"	16 ½"	16 ½"	16 ½"	16 ½"	16 ½"
Spinner Size	15 ½"	15 ½"	15 ½"	15 ½"	15 ½"	15 ½"
Spreading Width	Up to 40'	Up to 40'	Up to 40'	Up to 40'	Up to 40'	Up to 40'
Materials	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix
Vehicle Application	3/4- & 1-Ton Pickup Trucks	3/4- & 1-Ton Pickup Trucks	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)

Metric	7' 1.5 cu yd	8' 2.0 cu yd	9' 3.0 cu yd	9' 4.5 cu yd	10' 4.5 cu yd	10' 6.0 cu yd
Body Side Length	2.13 m	2.44 m	2.74 m	2.74 m	3.05 m	3.05 m
Capacity	1.15 cu m	1.53 cu m	2.29 cu m	3.44 cu m	3.44 cu m	4.59 cu m
Hopper Construction	1.5 mm SS	1.5 mm SS	1.5 mm SS	1.5 mm SS	1.5 mm SS	1.5 mm SS
Dimensions Overall (LxWxH)	214 cm x 127 cm x 97 cm	244 cm x 127 cm x 84 cm	275 cm x 127 cm x 105 cm	275 cm x 178 cm x 120 cm	305 cm x 178 cm x 120 cm	305 cm x 178 cm x 138 cm
Dual 12V DC Sealed Motors	269.89 kg	278.96 kg	315.25 kg	369.68 kg	--	--
Gas 10.5 hp I/C Briggs & Stratton®	--	335.66 kg	371.95 kg	426.38 kg	437.72 kg	458.13 kg
Gas 11 hp I/C Honda®	--	335.66 kg	371.95 kg	426.38 kg	437.72 kg	458.13 kg
Dual Hydraulic Motors	--	278.96 kg	315.25 kg	369.68 kg	381.02 kg	401.43 kg



## Striker™ Specifications

Conveyor Width	42 cm	42 cm	42 cm	42 cm	42 cm	42 cm
Spinner Size	40 cm	40 cm	40 cm	40 cm	40 cm	40 cm
Spreading Width	Up to 12.19 m	Up to 12.19 m	Up to 12.19 m	Up to 12.19 m	Up to 12.19 m	Up to 12.19 m
Materials	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix	Salt, Sand, Salt/Sand Mix
Vehicle Application	3/4- & 1-Ton Pickup Trucks	3/4- & 1-Ton Pickup Trucks	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)	Dump Body or Flatbed Trucks (over 15,000 lb GVWR)