



## WIDE-OUT™ & WIDE-OUT™ XL Specifications

### Technical Specifications

Imperial	8'-10' (#180209-lower)	8'-10' (#180210-higher)	8'6"-11'
Blade Width	8' retracted 10' expanded 8' 10" scoop	8' retracted 10' expanded 8' 10" scoop	8' 6" retracted 11' expanded 9' 10" scoop
Blade Height	29"	31" on moldboard 35" at end	31" on moldboard 36" at end
Blade Gauge	12	14	14
Trip Springs	4	4	4
Vertical Ribs	6	6	8
Angling Rams	1½" x 10"	1½" x 10"	1½" x 10"
Plowing Width (full angle)	7' 2" retracted 9' expanded 7' 11" scoop	7' 2" retracted 9' expanded 7' 11" scoop	7'11" retracted 10' 6" expanded 9' 6" scoop
Approx. Weight (less mount)	940 lb	1020 lb	1090 lb
Disc Shoes	Optional	Optional	Optional
Cutting Edge	1/2" x 6" blade	1/2" x 6" blade	1/2" x 6" blade
Mount Type	UltraMount® 2	UltraMount® 2	UltraMount® 2
Lift Cylinder	1¾" x 8"	1¾" x 8"	1¾" x 8"
Shock Absorbers	No	Optional	Optional

Metric	8'-10' (#180209-lower)	8'-10' (#180210-higher)	8'6"-11'
Blade Width	2.44 m retracted 3.05 m expanded 2.69 m scoop	2.44 m retracted 3.05 m expanded 2.69 m scoop	2.59 m retracted 3.35 m expanded 3.00 m scoop
Blade Height	73.66 cm	78.74 cm 88.90 cm at end	78.74 cm on moldboard 91.44 cm at end
Blade Gauge	2.78 mm	2.11 mm	2.11 mm
Trip Springs	4	4	4
Vertical Ribs	6	6	8
Angling Rams	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Plowing Width (full angle)	2.18 m retracted 2.74 m expanded 2.41 m scoop	2.18 m retracted 2.74 m expanded 2.41 m scoop	2.41 m retracted 3.20 m expanded 2.90 m scoop
Approx. Weight (less mount)	426 kg	462.66 kg	494.42 kg
Disc Shoes	Optional	Optional	Optional
Cutting Edge	1.27 cm x 15.24 cm blade	1.27 cm x 15.24 cm blade	1.27 cm x 15.24 cm blade
Mount Type	UltraMount® 2	UltraMount® 2	UltraMount® 2
Lift Cylinder	4.45 cm x 20.32 cm	4.45 cm x 20.32 cm	4.45 cm x 20.32 cm
Shock Absorbers	No	Optional	Optional