



ENFORCER(TM) Specifications

Imperial	7' 6" SS	7' 6" PC
Blade Width	7' 6"	7' 6"
Blade Height	27" at Center 33" at End	27" at Center 33" at End
Blade Gauge	14 ga	14 ga
Trip Springs	2	2
Ribs	6 Vertical 2 Horizontal	6 Vertical
Lift Cylinder	1 ¼" x 8 5/8 "	1 ¼" x 8 5/8 "
Angling Rams	1 ½" x 12"	1 ½" x 12"
Plowing Width	6' 7" Full Angle 6' 5" Scoop 6' 9" Full V	6' 7" Full Angle 6' 5" Scoop 6' 9" Full V
Approx. Weight*	554 lb	509 lb
Cutting Edge	3/8 " x 6"	3/8 " x 6"
Mount Type	UltraMount® 2	UltraMount® 2

Metric	7' 6" SS	7' 6" PC
Blade Width	2.29 m	2.29 m
Blade Height	68.58 cm at Center 83.82 cm at End	68.58 cm at Center 83.82 cm at End
Blade Gauge	1.98 mm	1.98 mm
Trip Springs	2	2
Ribs	6 Vertical 2 Horizontal	6 Vertical
Lift Cylinder	3.18 cm x 21.91 cm	3.18 cm x 21.91 cm
Angling Rams	3.81 cm x 30.48 cm	3.81 cm x 30.48 cm
Plowing Width	2.01 m Full Angle 1.96 m Scoop 2.06 m Full V	2.01 m Full Angle 1.96 m Scoop 2.06 m Full V
Approx. Weight*	251.29 kg	230.88 g
Cutting Edge	0.95 cm x 15.24 cm	0.95 cm x 15.24 cm
Mount Type	UltraMount® 2	UltraMount® 2

SS = Stainless Steel | PC = Powder Coat

*Does not include vehicle mount. Please refer to the Quick Match program for specific vehicle applications.